



1. Features

- H.264 Video compression
- TVI/AHD/DVR/NVR Four in one, Multi-mode input, HD analog video encoding, support for high-definition analog and high-definition network video input, support pure HD network video input
- Using cloud services, easily achieve a variety of network penetration; one step to achieve remote monitoring, and no need various complicated network settings. It is convenient and easy operation
- Support mobile phone remote monitoring (iPhone /Android)
- Supports multiple web browsers (IE、 Chrome、 Firefox、 Safari)
- Supports VGA, TV and HDMI output simultaneously
- Powerful Network Services (Support DHCP、 PPPOE、 FTP、 DNS、 DDNS、 NTP、 UPNP、 EMAIL、 IP Competence、 IP Search 、 Alarm Center) ,Perfect matching (WEB、 Client、 SDK) ,Easy to achieve mutual-communication
- More than 20 kinds of languages supported (Arabic、 Brazilian、 Bulgarian、 Czech、 Dutch、 English、 Persian、 Finnish 、 French、 German、 Greek、 Hebrew、 Hungarian、 Indonesian、 Italian、 Japanese、 Polish、 Portuguese、 Romanian、 Russian、 Chinese Simplified、 Slovak、 Spanish、 Swedish、 Thai、 Chinese Traditional、 Turkish、 Vietnamese) ,no language restrictions
- Free replacement for boot interface and free selection for interface style

2. Application

Applicable to financial services, telecommunications, government, schools, airports, factories, hotels, museums, traffic monitoring, and other places

3. Specification

Model		BTG 9016
system	Video Compression	H.264
	Operating	Embedded Linux
Video	Input	16CH

	VGA output resolution	1440*900,1280*1024,1280*768,1280*720
	HDMI output resolution	1920*1080,1440*900,1280*1024,1280*768,1280*720
	BNC output	Yes
Audio	Audio input	1CH
	Audio out	1CH
	Intercom	Yes
Decoding	Encoding	16* 1080N/15
	Synchronous Playback	4 * 1080N/15
Network management	Network protocol	TCP/IP, DHCP, Cloud,P2P,DDNS, NTP, SMTP
Backup	USB HDD /U-disk	Yes
	USB DVD Burner	Yes
	Backup file format	DAV、 AVI
Remote Access	Browsers	YES, supports multiple web browsers
	CMS	YES, supports CMS3.0
	Mobile phone operating system	IPhone, Android
Alarm	Alarm input	NO
	Alarm output	NO
	Buzzer	Support
Storage	HDD number	1*4TB
	E-SATA	NO
PTZ	Protocol	PELCOP,PELCOD,LILIN,MINKING,NEON,STAR,VIDO,DSCP,VISCA,SAMSUNG,RM110,HY
	Control mode	Pan, Tilt, Zoom, Preset, Cruise, Trace
	UTC Protocol	HD-AHD,HD-FH,HD-HXST,HD-MY, HD-TVI
External interface	Network interface	10 / 100 Mbps Ethernet (RJ-45)
	Serial interface	1 RS-485
	USB interface	2*USB 2.0
Other	Remote control	Yes
	Power supply	DC12V / 2A
	Working temperature	-10°C ~60°C
	Humidity	10% ~ 90% Humidity
	Dimensions	299.5x245.58x48.9mm

